

### 3” Submersible Solar Pump, DC Submersible Well Pump (Plastic Impeller), BLSC

model	max.flow (m <sup>3</sup> /h)	max.head (m)	pump		solar panel		pump diameter (inch)	outlet(inch)
			voltage(v)	power(w)	open circuit voltage(v)	recommended power(w)		
3BLSC3-25-D24/200	3	25	DC24	200	20-50	340	3	1.25
3BLSC3-35-D24/300	3	35	DC24	300	20-50	500	3	1.25
3BLSC3.5-47-D48/400	3.5	47	DC48	400	30-96	600	3	1.25
3BLSC5-45-D48/500	5	45	DC48	500	30-96	800	3	1.25
3BLSC3.5-80-D48/600	3.5	80	DC48	600	30-96	800	3	1.25
3BLSC5.2-50-D48/600	5.2	50	DC48	600	30-96	800	3	1.25
3BLSC3.5-95-D48/750	3.5	95	DC48	750	30-96	1000	3	1.25
3BLSC5.2-50-D72/600	5.2	50	DC72	600	50-150	900	3	1.25
3BLSC3.5-80-D72/600	3.5	80	DC72	600	50-150	900	3	1.25
3BLSC3.5-95-D72/750	3.5	95	DC72	750	50-150	1020	3	1.25
3BLSC5.5-65-D72/750	5.5	65	DC72	750	50-150	1020	3	1.25
3BLSC7-46-D72/750	7	46	DC72	750	50-150	1020	3	1.25
3BLSC3.8-123-D72/1100	3.8	123	DC72	1100	50-150	1500	3	1.25
3BLSC5.2-75-D110/750	5.2	75	DC110	750	60-185	1000	3	1.25
3BLSC5.5-65-D110/750	5.5	65	DC110	750	60-185	1000	3	1.25
3BLSC7-46-D110/750	7	46	DC110	750	60-185	1000	3	1.25
3BLSC3.8-123-D110/1100	3.8	123	DC110	1100	60-185	1360	3	1.25
3BLSC6-84-D110/1100	6	84	DC110	1100	60-185	1360	3	1.25
3BLSC7.5-62-D110/1100	7.5	62	DC110	1100	60-185	1360	3	1.25
3BLSC3.8-155-D110/1300	3.8	155	DC110	1300	60-185	1800	3	1.25
3BLSC3.8-180-D110/1500	3.8	180	DC110	1500	60-185	2000	3	1.25
3BLSC6-125-D110/1500	6	125	DC110	1500	60-185	2000	3	1.25
3BLSC7.5-78-D110/1500	7.5	78	DC110	1500	60-185	2000	3	1.25